

Ref. **9PIEM**

Outdoor

High

Boots



The +

- *Padded ankles for snug fit.
- *Heel scuff cap inserts.
- *Footbridge supplying torsional rigidity.

PURCHASE PACKAGING

Référence	Taille	Carton
9PIEM38	38	6
9PIEM39	39	6
9PIEM40	40	6
9PIEM41	41	6
9PIEM42	42	6
9PIEM43	43	6
9PIEM44	44	6
9PIEM45	45	6
9PIEM46	46	6
9PIEM47	47	6

DESCRIPTION

Composite toecap
 Antipenetration textile Wellmax® sole
 External sole in double density PU/PU
 Fur interior
 Upper in split leather
 Malleolus reinforcement

SECTORS

- Mining
- Extracting Oil and Gas
- Energy
- Infrastructure, building industry

APPLICATIONS

Builder,
 Slater,
 Ramp agent,
 Luggage handler,
 Site supervisor,
 Docker, ...

TECHNICAL FEATURES

Color	Brown	Lining	Faux fur
Color 2	Beige		
Upper	Full grain leather		
Toecap	Composite		
Puncture resistant sole	Textile		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These boots can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the boots, when not in use, in a dry, clean and airy place. The tim influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

STANDARD(S)

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **LEC FI00362018**

Delivered by INTERTEK (0362) Centre Court Meridian Business Park Leicester Leicester LE19 1WD United Kingdom

**EPI CAT. II**

EN ISO 20345:2011

S3

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

SRC

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

CI

Shoe insulation against cold (30 minutes at $-20^{\circ}C$)

RETAILER STAMP